





## NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
- 2. FOCAL LENGTH: f=74.8mm ± 1%
- BACK FOCAL LENGTH(REF): bf=66.5mm
- CLEAR APERTURE: >90%
- SURFACE QUALITY: 40-20 SCRATCH-DIG 5.
- 6. CENTRATION: <3arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1mm
- 8. THICKNESS TOLERANCE: ±0.1mm
- COATING: BBAR Ravg<0.5% FROM 350nm-700nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM  $\frac{[in]}{mm}$ 

THIS DRAWING IS FOR INFORMATION ONLY NOT INTENDED FOR MANUFACTURING

	DATE	NAME		
TITLE: D=5	11/19/2009	WD	DRAWN	
PLA	11/24/2009	BW	ENG APPR.	
MATERIAL:	12/09/2009	DD	MFG APPR.	
MATERIAL.	DDODDIETA DV A ND CONFIDENTIAL			

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THORLABS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THORLABS, INC. IS PROHIBITED.

## THORLABS INC. PO BOX 366 NEWTON NJ

50.8 F=75.0 N-BK7 A COAT NO CONVEX LENS

SIZE REV. N-BK7 Α В SCALE: 1:1 SHEET 1 OF 1 DWG. NO. PART NO.

LA1145-A 4453-E01

3 2