





- NOTES/SPECIFICATIONS:
  1. DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH: f=49.8mm ± 1%
- 2. BACK FOCAL LENGTH(REF): bf=45.0mm
- CLEAR APERTURE: >90%
- SURFACE QUALITY: 40-20 SCRATCH-DIG 5.
- 6. CENTRATION: <3arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1mm
- 8. THICKNESS TOLERANCE: ±0.1mm
- COATING: BBAR Rayg<0.5% FROM 650nm-1050nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM  $\frac{[in]}{mm}$ 

THIS DRAWING IS FOR INFORMATION ONLY NOT INTENDED FOR MANUFACTURING

		ı	
AME D	ATE		
WD 11/1	9/2009 TITL	E	
BW 11/2	4/2009		
DD 12/0	9/2009 MA1	TE	
PROPRIETARY AND CONFIDENTIAL			

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THORLABS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THORLABS, INC. IS PROHIBITED.

	<b>THORL</b>	ABS	INC.	PO BOX 366
--	--------------	-----	------	------------

E: D=30.0 F=50.0 N-BK7 B COAT PLANO CONVEX LENS

ERIAL: SIZE REV. N-BK7 Α В SCALE: 2:1 SHEET 1 OF 1 DWG. NO. PART NO.

LA1102-B 4507-E01

3 2