



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=150.5\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf=148.4\text{mm}$
4. CLEAR APERTURE: $>90\%$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $<3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: VAR R $<0.25\%$ PER SURFACE FOR 532nm & 1064nm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION

| | NAME | DATE |
|----------|------|-----------|
| DRAWN | GG | 01/OCT/12 |
| APPROVAL | DD | 01/OCT/12 |

COPYRIGHT © 2012 BY THORLABS
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS

THORLABS
www.thorlabs.com

D=25.4 F=150 UV FUSED SILICA
PLANO CONVEX LENS, -YAG COAT

| | | | |
|----------|-----------------|-----|---|
| MATERIAL | UV FUSED SILICA | REV | A |
|----------|-----------------|-----|---|

| | | | |
|--------|------------|---------------|---------|
| ITEM # | LA4874-YAG | APPROX WEIGHT | 0.03 kg |
|--------|------------|---------------|---------|